



SUNNY

SHANGHAI SUNNY ELEVATOR

ADD:1st Floor, Building 5, No. 1555 West Jinshajiang Road, Shanghai

TEL:86-13661864321

FAX:+86-21-59168286

<http://www.sunnyelevator.com>

<http://www.elevator-component.com>

<http://sh-esunny.en.alibaba.com>

<http://sh-esunny.en.made-in-china.com>

EMAIL:sunny@esunny-sh.com

SUNNY
SHANGHAI SUNNY ELEVATOR



**SHANGHAI
SUNNY
ELEVATOR**

Elevator/Escalator

A Safety Elevator Environment From SUNNY



COMPANY PROFILE

A wonderful style bears a kind of high-grade life. Though we can not define what life means. We shall choose high grade life.

SUNNY Elevator opens a window of the world by high tech.

It is competitive in the global markets because of the high quality.

Let's listen to the bell comes from the Bank of the Rhine river in Germany, feel the gorgeous charm of magical art in the air.

We always pursue our objectives as time goes by.

SUNNY Elevator is always engaged in researching into, developing, manufacturing various building traffic and transport systems such as elevator, escalator, moving walk etc. Through the centurial trials and hardships, SUNNY Elevator never changes its advanced technology.

SUNNY Elevators safely operate in all kinds of high grade buildings in over 100 countries and regions. As time flies, it continues the rigorous and conscientious spirits of the German nation, SUNNY Elevator popular-fixes the most superb elevators and escalators all over the world and opens the gate of the artistic elevator palace.

As a distinguished figure in the contemporary elevator industry, SUNNY Elevator witnesses the past and strides forwards a bright future. It connects classical German art with the advanced modern technology. It links the western european buildings with the eastern chinese style buildings.

From now on, space talks to light, aesthetics combines with high tech. Grace integrates with comfortable operation. It wholeheartedly creates a smooth urban sight line. It starts a big vision of SUNNY brand.

As a professional "one-stop" elevator and escalator solution plan supplier, Shanghai SUNNY elevator Co.,Ltd. integrates the elevator research, development, design, manufacture, sales, installation, repair, maintenance, transformation into one.

SUNNY Elevator is located in the most economically prosperous Changjiang River Delta Economic Zone(Jiading District, Shanghai, China). It owns 20,000 square meters of modern factory zones in Jiangqiao Industrial Zone, Jiading District, Shanghai, China. Total investment is 50 million RMB. It builds up 80m high elevator test tower, 7 elevator test wells. It can annually produce 5,000 sets of various elevators and escalators.

SUNNY Elevator inherits the outstanding German manufacture technology. It introduces the advanced international manufacture installations, combines with pioneer German elevator design concept. The first-class R&D, design, production, site service groups bring about the secure, reliable, outstanding elevators and escalators for vast clients.

SUNNY Elevators accord with GB7588-2003 and European En81 standards. It passes ISO9001 International Quality System Certification. In normal production process, the strict and comprehensive product inspection and testing system ensures the superior elevators and escalators with excellent operation.

SUNNY Elevator provides modern cities with the international product standards and operation experiences by the superior services. With the vigorous support of advanced management and innovative technology, it integrates with the advantageous resources to enhance its strength. It leads the elevator industry. It offers you the extraordinary German experience. This is also the unchanged pursuit of SUNNY Elevator.


WE DO THE SUNNY ELEVATOR

Exhibition Footprint

“ Shanghai Sunny Elevator Co., Ltd, founded in 1992, is a 34-year professional manufacturer specializing in designing and producing Opto-Electro-Mechanical products. Sunny Elevator has started import and export since 2012. We have experience in exporting all kinds of elevator parts and complete elevator to 80 countries all over the world. ”



HIGH SPEED ELEVATOR



High Speed Elevator Construction Sketch




The Extremely Comfortable Travel

A shock-absorbing device is set between the car body and holder to isolate vibration. It superiorly buffers vibration during the elevator running process. It reduces the car vibration and prompts the conformable travel to vast passengers. The combined car wall connection ensures mute effects in the car , the stable and enclosed air pressure.

High Speed Serials Specification Table

Target market	The medium & high grade of the commercial buildings
Control system	VVVF
Traction machine	Permanent magnet synchronous & gearless
Door machine	VVVF door machine
Net car height	2800mm
Rated load(kg)	1050/1150/1250/1350/1600/2000
Rated speed(m/s)	2.5/3.0/4.0/5.0/6.0/7.0
Max.lighting height(m)	120/150/180/220/260/300
Max.group supervision No.	8

Car Vibration System



High speed elevator parameter table

Load (kg)	Speed (m/s)	Size of entrance (mm)	Size of car (mm)	Size of hoistway (mm)	Size of machine room (mm)	Overhead height (mm)	Pit depth (mm)	Max travelling height (mm)
800	2.5	800*2100	1400*1350*2450	2200*2250	3000*3700	5200	2200	150
1000	2.5	900*2100	1600*1400*2450	2200*2250	3000*3700	5200	2200	150
	3.0					5500	3100	150
	3.5					5800	3700	180
	4.0					6200	4000	180
1050	2.5	900*2100	1600*1500*2450	2200*2300	3000*3700	5200	2200	150
	3.0					5500	3100	150
	3.5					5800	3700	180
	4.0					6200	4000	180
1150	2.5	900*2100	1800*1400*2450	2450*2300	3200*3700	5200	2200	150
	3.0					5500	3100	150
	3.5					5800	3700	180
	4.0					6200	4000	180
1250	2.5	900*2100	1950*1400*2450	2600*2300	3200*3700	5200	2200	150
	3.0					5500	3100	150
	3.5					5800	3700	180
	4.0					6200	4000	180/210
1350	2.5	1100*2100	1950*1500*2450	2600*2350	3200*3700	5200	2200	150
	3.0					5500	3100	150
	3.5					5800	3700	180
	4.0					6200	4000	180/210
1600	2.5	1100*2100	1950*1750*2450	2600*2600	3200*4000	5200	2200	150
	3.0					5500	3100	150
	3.5					5800	3700	180
	4.0					6200	4000	150/210
2000	2.5	1100*2100	2000*1950*2450	2650*2800	3200*4000	5200	2200	150
	3.0					5500	3100	150
	3.5					5800	3700	180
	4.0					6200	4000	150/210


Note:Reference only, for detail information,please contact SUNNY elevator.

SMALL MACHINE ROOM ELEVATOR




It Fulfills Small Cost

Small volume traction machine combines with integrated controller, so that it makes the machine room size same with well size. It covers the equal area as that of the well. At the same time of reducing the machine room height it beautifies the building outlook. It fulfills super small standard of machine room space and building cost.



Small Machine Room Elevator Construction Sketch



Small machine room elevator parameter table

Persons	Load (kg)	Speed (m/s)	Net size of car(mm)	Net size of door(mm) D.WxD.H	Shaft size(mm)			Machine room size(mm)	
			C.WxC.DxD.H	2P Central opening	H.WxD.H	HR.H	PIT	MR.WxMR.D	MR.H
6	450	1.0	1400*850*2300	800*2100	2000*1500	4000	1500	2000*1500	2500
		1.5/1.75				4400			
8	630	1.0	1400*1100*2300	800*2100	2000*1720	4200	1500	2000*1720	2500
		1.5/1.75				4400			
10	800	1.0	1400*1350*2300	800*2100	2000*1970	4200	1500	2000*1970	2500
		1.5/1.75				4400			
		2.0				4800			
		2.5				4800			
13	1000	1.0	1600*1450*2300 1100*2100*2300 (Residence/stretcher elevator)	900*2100	2200*2120 2100*2500 (Residence/stretcher elevator)	4200	1500	2200*2120 2100*2500 (Residence/stretcher elevator)	2500
		1.5/1.75				4400			
		2.0				4800			
		2.5				4800			
		3.0				5200			
		3.5				5500			
		4.0				6000			
16	1250	1.0	1900*1450*2300	1100*2100	2500*2150	4200	1500	2500*2150	2500
		1.5/1.75				4400			
		2.0				4800			
		2.5				5200			
		3.0				5500			
		4.0				6000			
18	1350	1.0	1900*1550*2300	1100*2100	2500*2250	4200	1500	2500*2250	2500
		1.5/1.75				4500			
		2.0				4800			
		2.5				5200			
		3.0				5500			
		4.0				6000			
21	1600	1.0	1900*1800*2300	1100*2100	2500*2500	4200	1500	2500*2500	2500
		1.5/1.75				4500			
		2.0				4800			
		2.5				5200			
		3.0				5500			
		3.5				6000			
		4.0				6350			
26	2000	1.0	1900*1800*2300	1100*2100	2700*2500	4200	1500	2700*2500	2500
		1.5/1.75				4500			
		2.0				4700			
			1900*2200*2300	1100*2100	2700*2700	4700	1600	2700*2700	2500
						5000			


Note:Reference only, for detail information,please contact SUNNY elevator.

MACHINE ROOM-LESS ELEVATOR




Greatness in Trivialness Intellectual and Outstanding

SUNNY machine room-less elevator series resolves the restriction to the elevator in the construction, building cost, building design style, use range. At the same time of saving the space and cost, it provides the passengers with upper level intellectual, effective and stable travel.



Machine Room-less Elevator Construction Sketch



Machine room-less elevator parameter table

Persons	Load (kg)	Speed (m/s)	Net size of car(mm)	Net size of door(mm)	Shaft size(mm)		
			C.WxC.DxD.H	2P Central opening	H.WxH.D	HR.H	PIT
6	450	1.0	1100*1100*2300	800*2100	2050*1850	4200	1500
8	630	1.0	1400*1100*2300	800*2100	2250*1900	4200	1500
		1.5/1.75				4400	1600
10	800	1.0	1400*1350*2300	800*2100	2250*1950	4200	1500
		1.5/1.75				4400	1600
		2.0				4800	1800
		2.5				5000	2000
13	1000	1.0	1500*1550*2300	900*2100	2350*2150	4200	1500
		1.5/1.75				4400	1600
		2.0				4800	1800
		2.5				4800	2000
21	1600	1.0	1900*1800*2300	1100*2100	2850*2400	4500	1500
		1.5/1.75				4700	1600
		2.0				4900	1800
		2.5				5100	2000
26	2000	1.0	1900*2200*2300	1100*2100	2900*2600	4500	1500
		1.5/1.75				4700	1600
		2.0				4900	1800

Note:Reference only, for detail information,please contact SUNNY elevator.

SQUARE OBSERVATION ELEVATOR



Superior Car Wall

It adopt highly secure safety laminated glass. It is transparent. The passengers might appreciate the busy and prosperous city sight through the transparent car wall. Lamination layer in liminated glass resists radiation. It buffers sound-wave vibration and isolates the sound. Large area car wall glass design shows smooth and beautiful lines. It beautifies the elevator car outline. Furthermore, the buildings are attractive.

Super large viewing field


Full transparent lift car design can maximize the field of view. Through the visual extension,passengers can have a panoramic view of all the beautiful scenery.

Multiple lift car shapes

Round,square and rhombic and other lift car shapes are optional, perfectly corresponding to different architectural styles.



Square Observation Elevator Construction Sketch



Square machine room/machine roomless elevator parameter table

Persons	Load (kg)	Speed (m/s)	Net size of car(mm)	Net size of door(mm) D.WxD.H	Shaft size(mm)		
			C.WxC.DxD.H	2P Central opening	H.WxH.D	HR,H	PIT
6	450	1.0	1100*1100*2300	800*2100	2050*1850	4200	1500
8	630	1.0	1400*1100*2300	800*2100	2250*1900	4200	1500
		1.5/1.75				4400	1600
10	800	1.0	1400*1350*2300	800*2100	2250*1950	4200	1500
		1.5/1.75				4400	1600
		2.0				4800	1800
		2.5				4800	2000
13	1000	1.0	1500*1550*2300	900*2100	2350*2150	4200	1500
		1.5/1.75				4400	1600
		2.0				4800	1800
		2.5				4800	2000
21	1600	1.0	1900*1800*2300	1100*2100	2850*2400	4500	1500
		1.5/1.75				4700	1600
		2.0				4900	1800
		2.5				5100	2000
26	2000	1.0	1900*2200*2300	1100*2100	2900*2600	4500	1500
		1.5/1.75				4700	1600
		2.0				4900	1800

Note:Reference only, for detail information,please contact SUNNY elevator.

SEMICIRCLE OBSERVATION ELEVATOR



Outer Glass Hood

It harmoniously combines with the building and surroundingd. Panoramic elevator is part of the building. It also adds a mobile charming scene for the building.

Outstanding sound insulation


The structure of the lift car is further optimized, which facilitates the elevator to achieve excellent sound insulation effect and customers to have quiet and steady using experience.

Diversified decoration design

There are a series of optional materials and colors for hoistway doors, handles and lift car walls, thus truly realizing individualized customized serives.



Semicircle Observation Elevator Construction Sketch



Semicircle machine room/machine roomless elevator parameter table

Persons	Load (kg)	Speed (m/s)	Net size of car(mm)	Net size of door(mm) D.WxD.H	Shaft size(mm)			Machine room size(mm)	
			C.WxC.DxD.H	2P Central opening	H.WxH.D	HR.H	PIT	MR.WxMR.D	MR.H
8	630	1.0	1100*1600*2300	700*2100	2200*2185	4500	1500	2200*2185	2500
		1.5/1.75				4700	1600		
10	800	1.0	1200*1800*2300	800*2100	2300*2355	4500	1500	2300*2355	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
13	1000	1.0	1300*1950*2300	900*2100	2400*2535	4500	1500	2400*2535	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
16	1250	1.0	1400*2150*2300	900*2100	2500*2600	4500	1500	2500*2600	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
18	1350	1.0	1500*2150*2300	1000*2100	2600*2600	4500	1500	2600*2600	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
21	1600	1.0	1500*2450*2300	1000*2100	2600*2900	4500	1500	2600*2900	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
26	2000	1.0	1700*2600*2300	1100*2100	2800*3050	4500	1500	2800*3050	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		

Note:Reference only, for detail information,please contact SUNNY elevator.

HOSPITAL ELEVATOR



Warm Concern A Beautiful Humanity World


SUNNY hospital elevators are not just used in delivering passengers. Because of its use particularity, it has special and strict requirements to the elevator use properties. SUNNY hospital elevator can accurately control the elevators'running speed. It brings about the smooth and comfortable travel.

SUNNY hospital elevator lays special importance upon the humane design. It fully optimizes the car structure. It satisfies the clients' use requirements to the greatest extent. It creates a peaceful and graceful space for vast passengers.

SUNNY hospital elevator satisfies the needs of emergency patients' delivery. It applies humanization design and is equipped with a full set of top equipments. It is smooth and comfortable in running.




Hospital Elevator Construction Sketch



Hospital elevator parameter table

Persons	Load (kg)	Speed (m/s)	Net size of car(mm)	Net size of door(mm)	Shaft size(mm)			Machine room size(mm)	
			C.WxC.DxD.H	D.WxD.H	H.WxH.D	HR.H	PIT	MR.WxMR.D	MR.H
21	1600	1.0	1400*2400*2300	1100*2100	2550*2900	4500	1500	2550*2900	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
24	1800	1.0	1600*2400*2300	1200*2100	2750*2900	4500	1500	2750*2900	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
26	2000	1.0	1700*2400*2300	1200*2100	2850*2900	4500	1500	2850*2900	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		

Note:Reference only, for detail information,please contact SUNNY elevator.



PERFECT FUNCTION

★ Standard Function

 Travel Function	VVVF drive	Motor rotating speed can be precisely adjusted to get smooth speed curve in lift start, travel and stop and gain the sound comfort.
	VVVF door operate	Motor rotating speed can be precisely adjusted to get the more gentle and sensitive door machine start/stop.
	Independent running	The lift can not respond to outer calling, but only respond to the command inside the car through the action switch.
	Automatic pass without stop	When the car is crowded with the passengers or the load is close to preset value, the car will automatically pass the calling landing in order to keep maximum travel efficiency.
	Automatically adjust door opening time	Door-open time can automatically adjusted according to the difference between landing calling or car calling
	Reopen with hall call	In the door shutting process, press reopen with hall call button can restart the door.
	Express door closing	When the lift stops and opens the door, press door-shut button, the door will be closed immediately.
	Car stops and door open	The lift decelerates and levels, the door only opens after the lift comes to a complete stop.
 Safety Function	Command register cancel	If you press the wrong floor command button in the car, twice continuous pressing of same button can cancel the register.
	Photoelectric protection	In the door open and shut period, infrared light that covers the whole door height is used to probe the door protection device of both the passengers and objects.
	Designated stop	If the lift can not open the door in the destination floor out of some reason, the lift will close the door and travel to the next designated floor.
	Overload holding stop	When the car is overload, the buzzer rings and stops the lift in the same floor.
	Anti-stall timer protection	The lift stops operation due to slippery traction wire rope.
	Start protection control	If the lift does not leave door zone within the designated time after it gets started, it will stop the operation.
	Inspection operation	When the lift enters into inspection operation, the car travels at inching running.
	Fault self-diagnosis	The controller can record 62 latest troubles so as to quickly remove the trouble and restore the lift operation.
	Repeated door closing	If the lift can not close the door due to certain obstacle or interference, the lift will reopen, or re-shut the door until sundries are eliminated.
	Up/down over-run and final limit protection	The device can effectively prevent from the lift's surging to the top or knocking the bottom when it is out of the control. It results in the more safe and reliable lift travel.
 Man-machine Interface	Down over-speed protection device	When the elevator downs 1.2 times higher than the rated speed, This device will automatically cut off control power, stop the motor running so as to stop lift down at over-speed. If the lift continues to down at over-speed, and the speed is 1.4 times higher than rated speed, safety tongs act to force the lift stop in order to ensure the safety.
	Upward over-speed protection device	When the lift ups 1.2 times higher than rated speed, the device will automatically decelerate to brake the lift.
	Micro-touch button for car call and hall call	Novel micro-touch button is used for operation panel command button in the car and landing calling button.
	Floor and direction indicator car	The car shows the lift floor location and current travel direction.
 Man-machine Interface	Floor and direction indicator	The landing panel shows the lift floor location and current travel direction.

 Emergency Function	Emergency car lighting	Emergency car lighting automatically activated when there is power failure.
	Inching running	When the elevator enters into emergency electric operation, the car travels at low speed inching running.
	Five way intercom	Communication amid car, car top, elevator machine room, well pit and rescue duty room through walkie-talkie.
	Bell	In emergency conditions, if bell button above car operation panel is continuously pressed, electric bell rings on top of the car.
	Fire emergency return	If you start key switch in main landing or monitor screen, all the callings will be cancelled. The elevator directly and immediately drives to the designated rescue landing and automatically opens the door.
 Energy-saving Function	Car ventilation, light automatic shut off	If there is no calling or command signal within the stipulated time, the car fan and lighting will be automatically closed in order to save the energy.
	Remote shut-off	The elevator can be called to main landing (after finishing the service) through the key switch and automatically exists the service.

★ Optional Function

 Emergency Function	Leveling when power failure	In normal power failure, the chargeable battery supplies the elevator to power. The elevator drives to the nearest landing.
 Travel Function	Anti-nuisance	In the light elevator load, when three more commands appear, in order to avoid the unnecessary parking, all the registered callings in the car will be cancelled.
	Open the door in advance	When the elevator decelerates and enters into door open zone, it automatically opens the door to enhance the travel efficiency.
	Direct parking	It completely accords with distance principle with no crawling in the leveling. It greatly enhances the travel efficiency.
	Group control function	When three or more same model lift groups are controlled in use, the lift group can automatically choose the most appropriate response. It avoids the repeated lift parking, reduces the passengers' waiting time and increases the travel efficiency.
	Duplex control	Two sets of same model elevators can unanimously respond the calling signal through the computer dispatch. In this way, it reduces the passengers' waiting time to the greatest extent and enhances the travel efficiency as well.
	On-duty peak service	Within the preset on-duty time, upward transport from the home landing is extremely busy. The lifts are continuously dispatched to the home landing in order to satisfy on-duty peak service.
	Off-duty peak service	Within the preset off-duty period, the lifts are continuously dispatched to top floor in order to satisfy off-duty peak service.
	Door open time extending	Press special button in the car, the lift door keeps open for certain period of time.
	Car arrival gong	Arrival tong in the car top announces that the passengers arrive.
	Voice announcer	When the elevator normally arrives, voice announcer informs the passengers about the relevant information.
 Man-machine Interface	Car assistant operation box	It is used in the large loading weight lifts or the elevators with crowded passengers so that more and more passengers can use the car.
	Operation box for the handicapped	It is convenient for the wheelchair passengers and those who have vision problems.
	Intelligent calling service	The car command or hoist-way calling can be locked or connected through special Intelligent Input.
	IC card control function	All (partial) landings can only input car commands through IC card after authorization.
 Monitor Function	Remote monitor	The elevator long-distance monitor and control can be fulfilled through modem and telephone. It is convenient for the factories and service units to timely know the travel conditions of every elevator and promptly take the corresponding measures.
	Remote control	The lift car have independent travel according to the specific requirements through operation monitor screen (optional).
	Camera function in the car	The camera is installed in the car to monitor the car conditions.

STANDARD CONFIGURATION



SN-CD-106 Standard

Stainless steel car

Ceiling: SN-CC-509 style, arched top-plate, bright lighting

Car wall: Hairline stainless steel

Operation panel: SN-COP-010

Car door: Hairline stainless steel, center opening

Floor: SN-CF-601

Operation panel



SN-COP-010

Landing door



SN-DP-321



SN-DP-318



SN-DP-395

Ceiling



SN-CC-509


Arched top-plate, bright lighting



SN-CC-537

Central LED luminous panel, LED down lamps on both sides

Floor



SN-CF-601



SN-CF-603



SN-CF-604

Outbound call



SN-LOP-010



SN-LOP-010B

PASSENGER ELEVATOR CAR DECORATION

-ECONOMIC SERIES



SN-CD-108 Economic Solution

Ceiling: St.St frame with milk white acrylic lighting deco two sides.

Middle Panel: Mirror, Etching.

Side Panel: Hairline.

Handrail model: SN-CH-701



SN-CD-115

Ceiling: St.St frame with white acrylic lighting panel.

Middle Panel: Mirror.

Side Panel: Mirror, Etching.

Handrail model: SN-CH-711



SN-CD-118

Ceiling: St.St frame with white acrylic lighting panel.

Middle Panel: Mirror, Etching.

Side Panel: Hairline.

Handrail model: SN-CH-701



SN-CD-107

Ceiling: St.St frame with multi-layer lighting board, acrylic lighting deco.

Middle Panel: Mirror, Etching.

Side Panel: Hairline.


Handrail model: SN-CH-701



SN-CD-129



SN-CD-131



SN-CD-142



SN-CD-146



SN-CD-150



SN-CD-155



SN-CD-164



SN-CD-168



SN-CD-303

PASSENGER ELEVATOR CAR DECORATION


-ECONOMIC SERIES



^ SN-CD-E001



^ SN-CD-E002



^ SN-CD-E003



^ SN-CD-E010



^ SN-CD-E011



^ SN-CD-E012



^ SN-CD-E004



^ SN-CD-E005




^ SN-CD-E006



^ SN-CD-E013



^ SN-CD-E014



^ SN-CD-E015



^ SN-CD-E007



^ SN-CD-E008



^ SN-CD-E009



^ SN-CD-E016



^ SN-CD-E017



^ SN-CD-E018

PASSENGER ELEVATOR CAR DECORATION

-MODERN SERIES



SN-CD-113 Modern Solution

Ceiling: St.St frame with white acrylic lighting panel.
Middle Panel: Mirror, Hairline, Etching.
Side Panel: Mirror.



SN-CD-109

Ceiling: St.St frame with green white acrylic lighting panel.
Middle Panel: Mirror, Etching, Hairline, Concave Green.
Side Panel: Mirror, Etching, Hairline, Concave Green.



SN-CD-110

Ceiling: St.St frame with white acrylic lighting panel.
Middle Panel: Mirror, Etching.
Side Panel: Pasted Wooden Deco.
Handrail model: SN-CH-709



SN-CD-112

Ceiling: St.St frame with white painted acrylic lighting panel.
Middle Panel: Mirror, Etching.
Side Panel: Mirror.



SN-CD-153



SN-CD-429



SN-CD-432



SN-CD-501



SN-CD-434



SN-CD-502



SN-CD-503



SN-CD-K106



SN-CD-K107

PASSENGER ELEVATOR CAR DECORATION

-MODERN SERIES



SN-CD-M001



SN-CD-M002




SN-CD-M003




SN-CD-M010




SN-CD-M011



SN-CD-M012



SN-CD-M004



SN-CD-M005




SN-CD-M006



SN-CD-M013



SN-CD-M014




SN-CD-M015



SN-CD-M007




SN-CD-M008



SN-CD-M009



SN-CD-M016



SN-CD-M017



SN-CD-M018

PASSENGER ELEVATOR CAR DECORATION

-MODERN SERIES



^ SN-CD-M019



^ SN-CD-M020




^ SN-CD-M021



^ SN-CD-M028



^ SN-CD-M029



^ SN-CD-M030



^ SN-CD-M022



^ SN-CD-M023



^ SN-CD-M024



^ SN-CD-M031



^ SN-CD-M032



^ SN-CD-M033



^ SN-CD-M025



^ SN-CD-M026



^ SN-CD-M027



^ SN-CD-M034



^ SN-CD-M035




^ SN-CD-M036

PASSENGER ELEVATOR CAR DECORATION

-MODERN SERIES



SN-CD-M037



SN-CD-M038




SN-CD-M039



SN-CD-M046




SN-CD-M047



SN-CD-M048



SN-CD-M040



SN-CD-M041



SN-CD-M042



SN-CD-M049



SN-CD-M050




SN-CD-M051



SN-CD-M043



SN-CD-M044



SN-CD-M045



SN-CD-M052



SN-CD-M053



SN-CD-M054

PASSENGER ELEVATOR CAR DECORATION

-LUXURY SERIES



SN-CD-407 *Luxury Solution*

Condole top: Mirror stainless steel border, medium is white organic transparent board

Center plate: leather soft bag

Auxiliary plate: mirror, etch, stainless steel

Handrail: organic glass armrest

Floor: 2mmPVC spline.(optional marble)



SN-CD-409

Condole top: four sides wooden adornment frame, middle mirror titanium, concealed light, LED illum.

Center board: leather soft bag, wood decoration

Auxiliary board: Center of the mirror titanium, surrounding wood decorative frame

Handrail: titanium garden handrail


SN-CD-400

Ceiling: titanium mirror stainless steel, common roof, lamp lighting

Center plate: mirror, and grain, titanium

Auxiliary board: mirror, and grain, titanium

Handrail: wood and titanium combination round tube handrail



SN-CD-410

Condole top: wooden condole top border, tube lamp illum

Back wall: Wood veneer, advertising frame, mirror stainless steel (self-care of advertising drawing customers)

Side wall: wood decoration, cloth art

Handrail: stainless steel leather armrest



SN-CD-411



SN-CD-413



SN-CD-414




SN-CD-415



SN-CD-419




SN-CD-421



SN-CD-422



SN-CD-441



SN-CD-442

PASSENGER ELEVATOR CAR DECORATION

-LUXURY SERIES



SN-CD-L001



SN-CD-L002



SN-CD-L003



SN-CD-L010



SN-CD-L011




SN-CD-L012



SN-CD-L004



SN-CD-L005




SN-CD-L006



SN-CD-L013



SN-CD-L014



SN-CD-L015



SN-CD-L007



SN-CD-L008




SN-CD-L009



SN-CD-L016



SN-CD-L017



SN-CD-L018

PASSENGER ELEVATOR CAR DECORATION

-LUXURY SERIES



^ SN-CD-L019



^ SN-CD-L020



^ SN-CD-L021



^ SN-CD-L028



^ SN-CD-L029



^ SN-CD-L030



^ SN-CD-L022



^ SN-CD-L023




^ SN-CD-L024



^ SN-CD-L031



^ SN-CD-L032



^ SN-CD-L033




^ SN-CD-L025



^ SN-CD-L026




^ SN-CD-L027



^ SN-CD-L034



^ SN-CD-L035



^ SN-CD-L036

PANORAMIC ELEVATOR CAR DECORATION



SN-CD-912 Economic Solution

Upper and lower cover: Steel plate spraying
 Sightseeing wall: Safety clip glass
 Decorative top: HM-427 ceiling
 Cage wall: Safety clip glass
 Handrail: Stainless steel plate
 Floor: PVC floor

ECONOMIC SERIES



SN-CD-901

Upper&Bottom Canopy: Hairline
 Viewing Glass: Laminated Glass(2Layers)
 Cabin Wall: Hairline St./St
 Handrail: St./St. Tube
 Floor: PVC

SN-CD-902

Upper&Bottom Canopy: Hairline
 Viewing Glass: Laminated Glass(2LAYERS)
 Cabin Wall: Hairline St./St
 Handrail: St./St. Tube
 Floor: PVC




SN-CD-910

Upper & Bottom Canopy: Hairline with Light Deco
 Viewing Glass: Laminated Glass(2 Layears)
 Cabin Wall: Hairline St./St
 Handrail: St./St. Tube
 Floor: PVC



SN-CD-313

Upper and lower cover: Steel plate spraying with acrylic decorative strip
 Sightseeing wall: Three pieces of safety glue glass
 Decorative top: Image board and the lantern on both sides
 Cage wall: Stainless steel plate
 Handrail: Stainless steel double pipe
 Floor: PVC floor




SN-CD-314

Upper and lower cover: Steel plate spraying
 Sightseeing wall: Three pieces of safety glue glass
 Decorative top: Image board and the lantern on both sides
 Cage wall: Stainless steel plate
 Handrail: Stainless steel double pipe
 Floor: PVC floor

SN-CD-966

Upper & Bottom Canopy: Baked Enamel
 Viewing Glass: Laminated Glass(3Pcs)
 Cabin Wall: Hairline Etching Etching St./St
 Handrail: St./St. Tube
 Floor: PVC



PANORAMIC ELEVATOR CAR DECORATION

SN-CD-940

Modern Solution

Center plate: Mirror, stone relief, titanium

Auxiliary board: Wood grain relief



MODERN SERIES



SN-CD-934

Center plate: Hairline , etching

SN-CD-941

Upper & Bottom Canopy: Baked Enamel

Viewing Glass: Laminated Glass(3Pcs)

Cabin Wall: Hairline Etching St./St

Handrail: St./St. Tube

Floor: PVC



SN-CD-933

Upper & Bottom Canopy: Semicircular Acrylic Crown with Metal Cover and Steel Plate

Spraying Coaming

Viewing Glass: Laminated Glass(3Pcs)

Cabin Wall: Stainless steel hairline

Handrail: Stainless steel double tube

Floor: PVC



SN-CD-945

Upper & Bottom Canopy: Steel paint,Lighting

Viewing Glass: Sandwiched glass

Decorative top:Steel paint,Acrylic roof,Lighting

Cabin Wall: Stainless steel process tube

Handrail: Stainless steel tube

Floor: PVC



SN-CD-980

Upper and lower cover: Ladder pentagon steel paint and decorative lights

Sightseeing wall: Safety laminated glass

Decorative top: Middle round acrylic top

lamp,Simple lights on both sides

Cage wall: Stainless steel hair plate

Handrail: Single stainless steel tube

Floor: PVC floor



SN-CD-981

Upper and lower cover: Steel plate spraying

Sightseeing wall: Three pieces of safety glue glass

Decorative top: Multi-layer reflective process board plus simple light

Cage wall: Stainless steel hairline

Handrail: Stainless steel single tube

Floor: PVC floor

PANORAMIC ELEVATOR CAR DECORATION



SN-CD-961 *Luxury Solution*

Upper&Bottom Canopy: Baked Enamel with Light Deco
Viewing Glass: Laminated Glass(3Pcs)
Cabin Wall: Golden Mirror Etching St./St
Handrail: St./St. Tube
Floor: PVC

LUXURY SERIES



^ SN-CD-962

Upper&Bottom Canopy: Half Round Baked Enamel with Acrylic Cop. light Deco
Viewing Glass: Laminated Glass(3Pcs)
Cabin Wall: MIRROR Etching St./St
Handrail: St./St. Tube
Floor: PVC



^ SN-CD-974

Upper and lower cover: Organic plate with metal strip and five deformation steel plate
Sightseeing wall: Safety clip glass
Decorative top: Image board with tube lamp
Cage wall: Mirror, hair line, etching, concave gold
Handrail: Stainless steel double pipe
Floor: PVC floor

^ SN-CD-963

Upper&Bottom Canopy: Hairline Round
Viewing Glass: Laminated Glass(3Pcs)
Cabin Wall: Mirror Etching St./St
Handrail: St./St. Tube
Floor: PVC



^ SN-CD-964

Upper&Bottom Canopy: Baked Enamel with Light Deco
Viewing Glass: Laminated Glass(3Pcs)
Cabin Wall: Golden Mirror Etching St./St
Handrail: St./St. Tube
Floor: PVC



^ SN-CD-976

Upper and lower cover: Terraced round plate baking paint with decorative lights
Sightseeing wall: Three pieces of safety glue glass
Cage wall: Stainless steel titanium plate
Handrail: Stainless steel single pipe
Floor: PVC floor



^ SN-CD-978

Upper and lower cover: Semicircle acrylic crown and stainless steel coaming
Sightseeing wall: Three pieces of safety glue
Decorative top: Multi-layer reflective process board with tube lamp
Cage wall: Mirror, hair, etching, and grain
Floor: PVC floor

OPERATION PANEL



SN-COP-012 **Standard Solution**

Optional display



Optional button



Direction lantern



Operation panel series



SN-COP-080 **Economic Solution**



SN-COP-020 **Modern Solution**



SN-COP-102 **Luxury Solution**

ELEVATOR CEILING SERIES




SN-CC-501

White arch light-emitting panel, stainless steel mirror frame, strip light decoration




SN-CC-502

Titanium gold stainless steel mirror base-plate is supplemented with rectangle hollow transparent light pole, central soft lighting design of white organic panel



SN-CC-503

Stainless steel mirror hollow panel, white organic panel, mirror stainless steel frame



SN-CC-519

Round art panel model, rear soft lighting design of down lamp



SN-CC-520

Round steel bar model, white organic panel, rear soft lighting design of down lamp



SN-CC-521

Round hollow art panel model, rear soft lighting design of down lamp



SN-CC-504

Stainless steel titanium gold mirror hollow panel, white light-emitting panel, mirror stainless steel frame



SN-CC-505

Stainless steel mirror hollow panel, white organic panel, mirror stainless steel frame



SN-CC-506

Stainless steel mirror hollow panel, white organic panel, aluminum alloy frame



SN-CC-522

Round glass model, rear soft lighting design of down lamp



SN-CC-523

Round lotus pattern art panel, rear soft lighting design of down lamp



SN-CC-524

Central white ceiling lamp, four-side stainless steel base plate with soft lighting design of down lamp



SN-CC-507

Stainless steel mirror hollow panel, white organic panel, aluminum alloy frame



SN-CC-508

Mirror stainless steel panel is supplemented with rectangle hollow transparent light pole, central soft lighting design of white organic light-emitting panel



SN-CC-510

Central image arch, two-side stainless steel base-plate is supplemented with soft lighting design of down lamp (image to be provided by client)



SN-CC-527

Stainless steel frame, white acrylic light-emitting




SN-CC-528

Stainless steel square tube frame, mirror stainless steel, down light




SN-CC-529

Stainless steel side frame + soft lighting design of arch white light-emitting panel




SN-CC-511

Soft lighting design of broad arch white light-emitting panel



SN-CC-515

Central image arch, two-side stainless steel base plate, soft lighting design of down lamp



SN-CC-518

Soft lighting design of broad image arch




SN-CC-530

Stainless steel side frame + soft lighting design of arch white light-emitting panel



SN-CC-531

Stainless steel square tube frame, mirror stainless steel, down light



SN-CC-532

Stainless steel side frame + soft lighting design of arch white light-emitting panel

ELEVATOR PANEL SERIES



SN-DP-301 **Standard Solution** 
Mirror, Hairline, Etched



SN-DP-302 **Standard Solution** 
Mirror, Etched



SN-DP-334 **Standard Solution** 
Mirror, Etching, Concave Golden



SN-DP-343 **Economic Solution** 
Mirror, Etched, Hairline



SN-DP-347 **Economic Solution** 
Mirror, Etched, Hairline



SN-DP-348 **Economic Solution** 
Mirror, Etched



SN-DP-337 **Standard Solution** 
Mirror, Etching, Golden, Hairline



SN-DP-356 **Standard Solution** 
Mirror, Etching, Hairline



SN-DP-363 **Standard Solution** 
Mirror, Etching, Hairline, Concave Golden



SN-DP-323 **Luxury Solution** 
Mirror, Etched, Rose gold



SN-DP-336 **Luxury Solution** 
Mirror, Etched, Titanium Golden



SN-DP-339 **Luxury Solution** 
Mirror, Etched



SN-DP-427 **Standard Solution** 
Titanium, Mirror, Etching



SN-DP-321 **Standard Solution** 
Mirror, Hairline




SN-DP-322 **Economic Solution** 
Mirror, Etched



SN-DP-388 **Luxury Solution** 
Mirror, Etching, Titanium Golden



SN-DP-395 **Luxury Solution** 
Mirror, Etching, Titanium Golden




SN-DP-396 **Luxury Solution** 
Mirror, Hairline, Titanium Golden

ELEVATOR FLOOR SERIES



SN-CN-601



SN-CN-602



SN-CN-603



SN-CN-604



SN-CN-605




SN-CN-606



SN-CN-615



SN-CN-616



SN-CN-620



SN-CN-621



SN-CN-609



SN-CN-610



SN-CN-613



SN-CN-614



SN-CN-696

OPTIONAL COLORS



ice gray

SN-SK001
PAL 7047



plane gray

SN-SK002
PAL 7040



comy yellow

SN-SK003
PAL 1015



pebble gray

SN-SK004
PAL 7032



ultramarine blue

SN-SK005
PAL 5002



pastel blue

SN-SK006
PAL 5024



light green

SN-SK007
PAL 6021



light pink

SN-SK008
PAL 3015

ELEVATOR HANDRAIL SERIES





SN-CH-701



SN-CH-703



SN-CH-711



SN-CH-702



SN-CH-704



SN-CH-709



SN-CH-707

FREIGHT ELEVATOR



✔ A loading giant that can release more and more cargo pressures for you

SUNNY freight lift serial fully utilizes the advanced and fully computerized contrl technology. It employs the well-developed VVVFcontrol system of SUNNY elevator. It is sample in structure and convenient in repair and maintenance. It fulfiles a qualitative leap in the aspects of the signal transmission and running control. It brings about the more stable ans reliable system, the lower noise, the smoother running, the more accurate leveling. It is more and more easy for the goods entry and exit. In addition, SUNNY freight lift serial can offer the micro-processor. The high speed running capabilities and expansion interface ensure to satisfy the special requirements from broad users.

✔ Light curtain protection


Several protective light curtains are formed at the entrance of the elevator, which sensibly detects and responses to any objects that intrude into the detecting scope. The safety of human and cargoes are guaranteed.

✔ The extremely humane operation

It is equipped with fully automatic collective selective function. It can fulfill operation with driver / without driver. The operation box specially and additionally sets"door-shut delay" button in the operation box. Door-shut delay time can be flexibly adjusted at site according to the requirements. You feel more at ease at loading and unloading the goods out of its humane setting.



Freight Elevator Construction Sketch



Freight elevator parameter table

Load (kg)	Speed (m/s)	Net size of car(mm)	Net size of door(mm)	Shaft net size(mm)			Machine room net size(mm)		Door open type
		C,WxC,DxD,H	D,WxD,H	width x depth	Overhead height	Pit depth	width x depth	height	
630	0.5	1200*1500*2200	1100*2100	2100*1860	4200	1500	2500*3000	2200	Two panel side opening
1000	0.5	1500*1800*2200	1200*2100	2250*2160	4200	1500	3000*3000	2200	Two panel side opening
2000	0.5	1570*2900*2200	1500*2100	2700*3260	4200	1500	3500*3000	2500	Two panel side opening
	1.0				4500	1500			Two panel side opening
	1.5	2000*2300*2200		2850*2660	4500	1600			Four panel center opening
	2.0				4800	1800			Four panel center opening
3000	0.25	2070*3050*2200	1800*2100	3300*3410	4500	1500	3800*4200	2500	Four panel center opening
	0.5								
3200	1.0	2070*3100*2200	1800*2100	3300*3460	4500	1500	3800*4200	2500	Four panel center opening
5000	0.25	2800*3400*2500	2000*2200	4200*3800	5000	1600	4200*3800	2800	Four panel center opening
	0.5								Four panel center opening
7000	0.25	3000*4200*2500	2600*2400	4500*4600	5000	1600	4500*4600	2800	Four panel center opening
	0.5								Four panel center opening
10000	0.25	3070*5760*2500	2600*2400	4900*6200	5000	1600	4900*6200	2800	Four panel center opening

Note:Reference only, for detail information,please contact SUNNY elevator.

CAR ELEVATOR



Perfect Space for Cars

We develop and produce SUNNY automobile elevator through absorption, transformation and enhancement by introducing the world's, well-developed automobile elevation technology. The powerful technical capacity of SUNNY reduces the traction system burden due to uneven force to the elevator car. It solves the technical obstacle of shaking elevator car due to noise production. It optimizes the characteristics of the product series.



⌘ Dual operation panels design(Optional)

There are two operation box in the car. Therefore the driver can operate the elevator in the car without slapping out of it.



⌘ Special-purpose circuit control and display system


Special circuit control and display system is convenient for the drivers inside/outside the car.



⌘ Front-and-rear opening elevator car

The elevator car sets front/rear door opening which is more convenient for the safety sector and for the cars to enter into/exit from the elevator cars.

Car Elevator Construction Sketch




Car elevator parameter table

Load (kg)	Speed (m/s)	Door open type	Net door opening widthxheight(mm)	Exterior size of car widthxdepth(mm)	Shaft net size(mm)			Machine room net size(mm) widthxdepthxheight
					widthxdepth	pit depth	overhead height	
3000	0.25/0.5	Four Panel Center Opening	2400*2200	2700*5800	4100*6160	1600	4800	4100*6160*2500
5000	0.25 0.5	Four Panel Center Opening	2600*2200	3500*7200	4750*7560			4750*7560*2500

Note:Reference only, for detail information,please contact SUNNY elevator.

FREIGHT ELEVATOR
CAR DECORATION



Side Opening

◀ SN-CD-F100
(Standard)

Item	Specification
Car ceiling	Painted panel,energy-saving light
Ventilation	Square fan
Car wall	Painted panel(Standard) Hairline stainless steel(Optional)
Car door	Painted panel(Standard) Hairline stainless steel(Optional)
Floor	Checked stainless steel plate
Sill	Steel sill(Open width > 1500) Reinforced aluminum alloy(Open width≤1500)

SN-CD-F200 ▶
(Standard)

Item	Specification
Car ceiling	Painted panel,energy-saving light
Ventilation	Round fan
Car wall	Painted panel(Standard) Hairline stainless steel(Optional)
Car door	Painted panel(Standard) Hairline stainless steel(Optional)
Floor	Checked stainless steel plate
Sill	Steel sill(Open width > 1500) Reinforced aluminum alloy(Open width≤1500)



Double-folded Center Opening Type

▼ OPERATION PANEL




SN-COP-160

Operation panel:Hairline stainless steel

▼ FLOOR



Ordinary checked
steel plate I
(Standard)



Ordinary checked
steel plate II
(Optional)

▼ CRASH BARRIER



Wooden



Rubber

▼ LANDING DOOR



Center opening



Side opening



Double-folded
center opening type



3-Folded
center opening type


▼ POWDER COATING COLOR(OPTIONAL)




SN-SK001



SN-SK002



SN-SK003



SN-SK007

ESCALATOR



Perfect Model Brings About The Better Riding Experience

Extremely long life, energy efficient delivery, stable and reliable performance, will be on your right-hand man, is the best carrying tools. SUNNY escalator to the excellent performance, practical and flexible design to meet different customer needs. Priority use of microcomputer variable frequency(VVVF) and ergonomics research and advanced manufacturing technology, SUNNY escalator is more perfect, safe, comfortable, energy-saving, easy miantenance.

Optimized Design Saves The Space

Minimum span size greatly saves the occupied space. The compact pit depth design brings about a freer construction layout.

City Large-flow Traffic Solution Plan Specialist


It innovatively combines with human-centered ideas. It has the advanced stairway and belt design. It is smooth and comfortable in operation. Solemn and smooth handrail entry, traffic flow light appear bright and dynamic. It perfectly connects with inner/outer cover plates, skirting plate, frontline plate. It smoothly transits to big arc rotary end handrail.

SUNNY escalators are widely applicable for the airport, railway station, high grade hotel, CBD, large-size shopping center, public facilities etc. It adds a brilliant sight line for modern building.

- Its truss adapt the superior profile steel with unique structure, high intensity, through anti-rusting, good effect, long life.
- The advanced international manufacture craft, technology, general assembly, tooling guarantee the precise elevator path.
- Super-strong CPU master-board computer control executes rea-t-time monitor to the running conditions. It automatically stops at any abnormal conditions. It also promptly and automatically makes records, displays the trouble code.



30° ESCALATOR CONSTRUCTION SKETCH



Reacting force

Step width	600	800	1000	Remark
R1(KN)	3.5xL+15.5	4xL+17	4.5xL+18.5	L=m
R2(KN)	3.5xL+10	4xL+11	4.5xL+11.5	

Power meter(Step width 1000mm speed 0.5m/s)

5.5KW	8KW	11KW
1.5m<H≤3.2m	3.2m<H≤4.8m	4.8m<H≤6.0m

Table of rules of extension interior escalator's upper part


	Power				
	Step width	<15KW	15KW	2X11KW	2X15KW
Without VVVF	600	417	417		
	800	0	0	500	
	1000	0	0	500	800
With VVVF	600	417	417		
	800	0	200	500	
	1000	0	0	500	800

Standard specification and dimension

Model		SN-ES-600	SN-ES-800	SN-ES-1000
Step width	A	600	800	1000
Decorating width	B	1140	1340	1540
Construction open width	C	1200	1400	1600
Space between handrail	D	838	1038	1238
Construction open width	E	1778	1978	2178

Notes		Specification parameter	
* The layout drawing is suitable for the construction which the height is below 6m. * If the step width is 600mm, 417mm shall be extended at the up of the truss.	Type		SN-ES-600-30
			SN-ES-800-30
			SN-ES-1000-30
	Speed		0.5m / s
	Rise height		H≤6000mm
	Angle		30°
	Supporting R1		KN
	Supporting R2		KN
	Weight W		KN
Power	Power supply	Three-phase AC 380V 50HZ	
	Lighting supply	Single-phase AC 220V 50HZ	

35° ESCALATOR CONSTRUCTION SKETCH



Reacting force

Step width	600	800	1000	Remark
R1(KN)	3.5xL+15.5	4xL+17	4.5xL+18.5	L=m
R2(KN)	3.5xL+10	4xL+11	4.5xL+11.5	

Power meter(Step width 1000mm speed 0.5m/s)

5.5KW	8KW	11KW
1.5m<H≤3.5m	3.5m<H≤5.0m	5.0m<H≤6.0m

Table of rules of extension interior escalator's upper part

	Power				
	Step width	<15KW	15KW	2X11KW	2X15KW
Without VVVF	600	417	417		
	800	0	0	500	
	1000	0	0	500	800
With VVVF	600	417	417		
	800	0	200	500	
	1000	0	0	500	800

Standard specification and dimension

Model		SN-ES-600	SN-ES-800	SN-ES-1000
Step width	A	600	800	1000
Decorating width	B	1140	1340	1540
Construction open width	C	1200	1400	1600
Space between handrail	D	838	1038	1238
Construction open width	E	1778	1978	2178

Notes		Specification parameter	
* The layout drawing is suitable for the construction which the height is below 6m. * If the step width is 600mm, 417mm shall be extended at the up of the truss.	Type		SN-ES-600-35
			SN-ES-800-35
			SN-ES-1000-35
	Speed		0.5m / s
	Rise height		H≤6000mm
	Angle		35°
	Supporting R1		KN
	Supporting R2		KN
	Weight W		KN
Power	Power supply	Three-phase AC 380V 50Hz	
	Lighting supply	Single-phase AC 220V 50Hz	

MOVING WALK



Extremely strong conveying capacities

- Moving walk has extremely strong conveying capacity. It can satisfy the traffic requirements of modern people in various aspects. It is applicable for the airport, shopping center, hotel, recreation center etc.
- Its unique and innovative design has minimum requirements to the space. Its firm structure is strong enough for any kind of load. At the same time of conveying large-size shopping plaza and busy airport; bus station, it saves every piece of precious space. It fully considers the requirements of modern city traffic.
- 0-12° angle of inclination can be freely choice according to different use and enviroment in the building.

Perfect Experience, Whole Hearted Contribution of SUNNY Elevator


SUNNY moving walk suits the occasions of large passenger flow, long operation time, long-distance delivery of passengers; luggage and goods. It follows the world's high tech development trend. It applies the advanced manufacture craft & technology. It goes all out to put out SUNNY moving walk, 0~12° multiple styles are available for the users' free choices. SUNNY moving walks are widely applicable for available big shopping malls, aviation ports, super-markets, recreation centers etc. It solves big carring problems of large passenger flows. It satisfies long-distance walk, carrying of luggage cart; baby's cart; shopping cart; wheel chair for the disabled and so on. It is as easily as walking an firm an firm earth. It is greatly convenient for people's outing and shopping.

SUNNY moving walk on behalf of the new trend of industry-leading manufacturing, innovative, stylish, streamlined design and creative styling, make the product look gorgeous and dignified, dignity and style of the highlights with the support of the building, moving walk and architecture harmony between, seamless, complement to each other.

SUNNY moving walk shape luxurious, very stylish aesthetic, harmonious integration and the metropolis modern architecture and interior, the perfect interpretation of new state of the art technology, safe and reliable, energy saving, smooth and comfortable design concept.






12° MOVING WALK CONSTRUCTION SKETCH



Detail A

Detail B

Detail C



Power meter(Pedal width 1000mm speed 0.5m/s)

5.5KW	8KW	11KW
1.2m≤H≤3.0m	3.0m<H≤4.5m	4.5m<H≤6.0m
15KW		
6.0m<H≤7.0m		

Supporting strength parameter	Q	M	N	D	1400	1600
800	0.0039	9.5	4.5	E	2050	2250
1000	0.0045	11	5	F	1340	1540
Angle	Rise height	Middle support	La	Lb	Lc	
12°	From	To	33	34		
	1601	2663	-	-	-	-
	2664	5851	1	-	L/2	L/2
	5852	8000	1	1	L/3	L/3


Table of rules of extension interior moving walk's upper part

	Power			
	Step width	<19KW	19KW-2X11KW	2X15KW
Without VVVF	800	0	0	500
	1000	0	0	500
With VVVF	800	0	200	500
	1000	0	0	500

Supporting			
Without middle support (KN)	Single middle support (KN)	Double middle support (KN)	
R1=Lxq+M	R1=Lxq+M	R1=Lxq+M	
	R2=Lxq+N	R2=Lxq+N	
R2=Lxq+N	R3=(La+Lb)x1.3xq	R3=(La+Lb)x1.3xq	
	R4=(Lb+Lc)x1.3xq	R4=(Lb+Lc)x1.3xq	



Notes		Specification parameter	
*The layout drawing is suitable for the construction which the height is below 7m.		Type	SN-ES-800-12
			SN-ES-1000-12
		Speed	0.5m/s
		Rise height	H≤7000mm
		Angle	12°
		Supporting R1	KN
		Supporting R2	KN
		Weight W	KN
		Power supply	Three-phase AC 380V 50HZ
		Lighting supply	Single-phase AC 220V 50HZ

0° MOVING WALK CONSTRUCTION SKETCH



Detail A

Detail B



Power meter(Pedal width 1000mm speed 0.5m/s)

5.5KW	8KW	11KW
12m≤L≤50m	50m<L≤72m	72m<L≤100m

Table of rules of extension interior moving walk's upper part

	Power			
	Step width	<15KW	15KW-2X11KW	2X15KW
Without VVVF	800	0	0	500
	1000	0	0	500
With VVVF	800	0	200	500
	1000	0	0	300

Step width	800	1000	Step width	800	1000
R1	32KN	36KN	A	800	1000
R2	31KN	33KN	B	1038	1238
R3	49KN	55KN	C	1340	1540
R4	50KN	57KN	D	1400	1600
R5	43KN	51KN	E	1400	1600

Notes		Specification parameter	
* This drawing is applicable to the civil construction of moving walkways.		Type	SN-ES-800-0
			SN-ES-1000-0
		Speed	0.5m/s
		Horizontal span	L≤100000mm
		Angle	0°
		Supporting R1	KN
		Supporting R2	KN
		Weight W	KN
		Power supply	Three-phase AC 380V 50HZ
		Lighting supply	Single-phase AC 220V 50HZ


HOME LIFT



SN-VE001



SN-VE002



SN-VE003



SN-VE004

▲ Traction home elevator

The most mainstream traction drive is used, and has sensitive and convenient, smooth and comfortable operation, energy conservation and environmental protection advantages. Advanced machine-less structure, small area, low civil construction requirements meet the different types of villa structure.

▲ knapsack frame structure home elevator

Mainly for the narrow and very deep inside the villa well, but also 90 degrees angle double car door elevator is the best choice.

▲ Steel belt type home elevator

It applies the more durable, energy-saving, environment protection composite steel band, Special material package without lubrication; Stable operation, safe and reliable; Long service life.

▲ Strong drive home elevator

It adopts advanced elevator forced drive and digital control technology of variable frequency speed regulation, running smoothly, No need to counterbalance, without gearbox, small volume, easy to install, can completely realize no machine room, save cost and save more space.

SN-VE400

Beauty of hidden luxury
Exquisite design starts the ritual life

The joyful experience of taking an elevator can be seen as far as the eye can see, and the exquisite details run through from the inside to the outside. SUNNY SN-VE400 has a safer and more stable operating quality, and both appearance and talent endow life with a full sense of ceremony.

Super Quiet

Innovative motor lock device,
free to enter and exit silently

New Structure

Steel belt traction backpack frame structure



64% Shaft Utilization

Full release of car space

With Car Design

Make up for the structural defects of the L-shaped platform ladder, which is safer and more stable

Break Through The Limit Space

Bottomless pit design, the minimum top floor height is only 2400mm



A beautiful work,High quality
SUNNY SN-VE400




New-generation 15.6-inch high-definition smart screen



Same color painting, advanced color



Cherry red aluminum alloy frame



Fully hidden design of the inner parts of the hoistway



Soft art atmosphere light



3 side panoramic sightseeing

SN-VE500

Extraordinary style
Play a gorgeous new scene for home

With ingenuity, the details of SUNNY SN-VE500 are all luxurious textures; small spaces make great achievements, and outline the ultimate luxury atmosphere in a small space of 1m².

Extreme Space Utilization

950x950

Ultra-small shaft frame size



700x700

Corresponding car area



2700mm

Minimum top height


Innovative Shaft Structure

Steel belt traction drive + gantry car frame structure

silent Travel

Adopt innovative motor lock device


Upgraded Safety Performance




Smart Light Curtain



Automatic Re-leveling




One Touch Dial



Internet of Things

Perfect luxury and superior atmosphere
SUNNY SN-VE500



Promise ecological ceiling



Arc-shaped car wall interface



Integrated door handle



Dashboard details



Car handrail



High Strength Alloy Frame





SN-VE500/SN-VE400 adopts Austria's top TIGER electrostatic powder coating process to forge supercar paint quality, fine texture, and present a perfect and beautiful space atmosphere. The aluminum alloy frame is equipped with a variety of theme colors, rich in choices, suitable for any style of high-quality home.



○ White

● Brown

● Black


● Gold

Note: There may be differences between the printed color and the actual color, please refer to the actual object.


Austria top TIGER process
Colorful frame is comprehensive and excellent

Car Option

Car background panel (rock panel) SN-VE400 only



Car background panel (glass) SN-VE400 only




Ceiling series



※There is no price increase for the above ceilings, and they can be selected within the range allowed by the ladder type

Floor covering (PVC woven carpet)


Floor covering (slate)



※There is no price increase for the above PVC woven blankets, and you can choose within the range allowed by the ladder type

※The above car floor (stone slab) is an option for additional price

The recommended car is suitable for displaying SN-VE400



Blue Mountains
Ceiling: LED lights
Back wall: art glass
Side wall: aluminum alloy of the same color as the shaft + sightseeing glass
Floor: Art Woven Rug

Vast Galaxy
Ceiling: star ceiling
Back wall: art glass
Side wall: aluminum alloy of the same color as the shaft + sightseeing glass
Floor: Art Woven Rug

Glacier Glass
Ceiling: water corrugated top
Back wall: art glass
Side wall: aluminum alloy of the same color as the shaft + sightseeing glass
Floor: Art Woven Rug

Golden Years
Ceiling: aluminum alloy shape + downlight
Back wall: art glass
Side wall: aluminum alloy of the same color as the shaft + sightseeing glass
Floor: Art Woven Rug

Car Option

Human Machine Interface



MR-CP06
Apply SN-VE500




MR-HP08(Standard)



MR-HP01(Optional)



MR-HP03(Optional)



MR-CP07
Apply SN-VE400

Opening Door Type




Manual Door



Automatic Door

Civil Engineering Scheme

SN-VE400 Construction Drawing



SN-VE500 Construction Drawing

